

WL800 Max II

High capacity water dispenser for demanding environments



Delivering water excellence

The WL800 Max II is designed to meet the demand for cold and hot water in high usage areas. The intuitive paddle operation and tall dispensing area enable users to easily fill large containers. The ultraviolet (UV) system maintains water hygiene in large capacity tanks and provides a continuous supply of clean and refreshing water.

Advanced technology

Two great steps to fresh water from Waterlogic®:



Four stage reverse osmosis filtration

Providing an high level of filtration, reverse osmosis (RO) effectively removes contaminants and dissolved particles, leaving only safe drinking water.



UV sanitization

The re-circulating UV system sanitizes the water by reducing bacterial growth giving the reassurance of fresh clean drinking water.

Safe water guaranteed

The WL800 Max II professional grade UV light purification system removes bacteria from the water without the need for toxic chemicals, so that you can enjoy refreshing great tasting water in every glass.

Features

Membrane based reverse osmosis filtration system removes the highest level of impurity and contaminants like acid, salts, nitrates, pesticides and arsenic, for thoroughly purified water

Cold and hot dispensing options

Easy to clean and use faucets

Hot water safety mechanism to protect against accidental dispensing

Tall dispensing area designed to fill large water vessels, such as jugs, carafes and sports bottles

Re-circulating UV system, continuously maintains water hygiene

Sleek profile and clean lines enhance the look of most workplaces

Leak detection for peace of mind

Overfill protection prevents accidental spillage

Water options

cold



sparkling

ambient

hot



extra hot

Technical specifications

Types available

Freestanding

Dimensions

16.9" (W) x 49.2" (H) x 20.1" (D)

Dispensing area height

11.7"

Weight

95 lbs

Standard filtration supplied

Four stage RO (reverse osmosis) filtration

Purification system

UV lamp (4W)

Storage capacity

Room temperature: 3.7 gal

Cold: 4.2 gal

Hot: 1 gal (500W heater)

Production rate: ~50 gal/d (77°F, 138 kPa)

Compressor

110V/ 60Hz

Water temperatures settings

Cold: 41°F

Hot: 185°F

Number of users



Up to 60

Tested and certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

Waterlogic USA

Tel: 855-350-5518

100 Biddle Ave, Suite 203,
Newark, DE 19702

www.waterlogicusa.com

info@waterlogicusa.com

For more information, visit www.waterlogic.com